NSN 5905-00-666-2817

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-666-2817

Electrical Resistance: 125.000 ohms Resistance Tolerance In Percent: -10.000 to 10.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 425.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Resistance Tolerance In Percent: -10.000 to 10.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 425.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 425.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 425.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 425.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 425.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Tab, solder lug Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Reliability Indicator: Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Not established Terminal Length: 1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
1.500 inches Body Length: 8.500 inches Power Dissipation Rating In Watts: 310.000 free air
8.500 inches Power Dissipation Rating In Watts: 310.000 free air
Power Dissipation Rating In Watts: 310.000 free air
310.000 free air
For Default.
Err Default:
0.500 inches
Style Designator:
Radial terminal each end
Test Data Document:
81349-milr15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-15109 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0