

View Online at <https://aerobasegroup.com/nsn/5905-00-666-4070>

**Section Quantity:**

3

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

1.5620 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

1.562 inches

**Undercut Width:**

0.0730 inches

**Body Diameter:**

1.757 inches

**Shaft Diameter:**

Between 0.2498 inches and 0.250 inches

**Shaft Length:**

0.625 inches

**Body Length:**

2.131 inches

**Mounting Lip Diameter:**

1.7500 inches

**Mounting Lip Depth:**

0.0930 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

354.0

**Maximum Starting Torque:**

1.50 inch-ounces

**Maximum Running Torque:**

0.80 inch-ounces

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

5.000 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-1.00/+1.00 all sections

**Power Dissipation Rating Per Section In Watts:**

2.5 free air all sections

**Function Conformity Per Section:**

All sections terminal base linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 all sections

**Terminal Type And Quantity:**

9 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0