NSN 5905-00-672-1310

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-672-1310
Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.136 inches
Shaft Diameter:
Between 0.124 inches and 0.126 inches
Shaft Length:
Between 1.156 inches and 2.156 inches
Body Length:
2.062 inches
Body Width:
0.875 inches
Body Height:
2.314 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
1.344 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
3.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-6.66 to 6.66 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
10001-1486148 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:

3 tab, solder lug

NSN 5905-00-672-1310

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0