NSN 5905-00-672-2761

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-672-2761

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.062 inches
Shaft Length:
0.125 inches
Body Length:
1.250 inches
Body Width:
0.250 inches
Body Height:
0.328 inches
Shaft Style:
Round, knurled
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
350.0
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
25.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
350.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:

Stops

NSN 5905-00-672-2761

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Supplementary Features:

5 oct. 00 item reviewed under girder project; country non concur cancellation action

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0