## NSN 5905-00-672-2798

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-672-2798 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.219 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.187 inches **Shaft Style:** Round, slotted Switch Type: Rotary **Switch Voltage Rating In Volts:** 250.0 **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Double pole, single throw, normally closed **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** 

Rear end **Mounting Method:** 

Standard bushing

## NSN 5905-00-672-2798

Precision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:
Switch
Electrical Resistance Per Section:
50.000 kilohms single section
Function Conformity Tolerance Per Section:
1.00/+1.00 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Function Characteristic Per Section:
Single section linear
Switch Current Type And Rating In Amps:
1.000 ac/dc
Terminal Type And Quantity:
7 tab, solder lug
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A002a0