

View Online at <https://aerobasegroup.com/nsn/5905-00-675-9552>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.9683 inches and 0.9688 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Overall Length:

1.312 inches

Undercut Diameter:

0.975 inches

Undercut Width:

0.0570 inches

Body Diameter:

1.125 inches

Shaft Diameter:

0.125 inches

Shaft Length:

Between 0.469 inches and 0.531 inches

Body Length:

0.906 inches

Overall Diameter:

1.359 inches

Mounting Lip Diameter:

Between 1.0570 inches and 1.0670 inches

Mounting Lip Depth:

Between 0.0570 inches and 0.0670 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

0.25 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00200 inches

Shaft Radial Play:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Function Conformity Per Section:

Single section terminal base linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-0.5/+0.5 ohms single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Tap Location From Ccw Terminal Per Section In Ohms:

2500.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0