NSN 5905-00-676-5068

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-676-5068 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.500 inches First Flat Length: 0.375 inches Flat Height: 0.216 inches **Body Diameter:** 1.969 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.969 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.500 inches **Overall Diameter:** 2.032 inches **Shaft Style:** Round, flatted Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 165.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:**

Nonturn Device Radius:
0.531 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Double pole, double throw

NSN 5905-00-676-5068

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
20.000 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
42.5 single section and 82.5 single section and 122.5 single section
Rotary Actuator Travel In Angular Deg:
170.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
1.7 free air single section
Fixed Tap Quantity Per Section:
3 single section
Tap Location Tolerance Per Section:
-1.0 to 1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Switch Current Type And Rating In Amps:
3.000 ac
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
12 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-676-5068

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



_					
11	em)	 tor	172	n	

No

Fiig:

A002a0