

View Online at <https://aerobasegroup.com/nsn/5905-00-676-7920>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Overall Length:

Between 0.490 inches and 0.510 inches

Terminal Length:

Between 0.170 inches and 0.210 inches

Overall Height:

Between 0.490 inches and 0.510 inches

Overall Width:

0.445 inches

Mounting Hole Diameter:

Between 0.070 inches and 0.076 inches

Shaft Diameter:

Between 0.092 inches and 0.097 inches

Shaft Length:

Between 0.058 inches and 0.085 inches

Body Length:

Between 0.490 inches and 0.510 inches

Body Width:

Between 0.250 inches and 0.265 inches

Body Height:

Between 0.490 inches and 0.510 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Maximum Starting Torque:

7.50 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Lateral Distance Between Mounting Hole Centers:

0.520 inches

Mounting Facility Quantity:

2

Terminal Location:

Left adjacent side single row

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

50.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.095 inches and 0.105 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

O-ring seal around shaft required. Device may be silicone filled

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0