

View Online at <https://aerobasegroup.com/nsn/5905-00-676-8208>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

Between 1.296 inches and 1.328 inches

Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.485 inches and 0.515 inches

Mounting Bushing Length:

Between 0.359 inches and 0.391 inches

Body Length:

Between 0.695 inches and 0.715 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

352.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

0.75 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

Between 0.557 inches and 0.567 inches

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Pilot Diameter Runout:

0.002 inches

Shaft Radial Play:

0.004 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Upper adjacent side two rows

Mounting Method:

Standard bushing

Center To Center Distance Between Terminal Rows:

0.188 inches

Electrical Resistance Per Section:

50.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

2.75 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0