## NSN 5905-00-676-8670

**Section Quantity:** 

Cylindrical bushing mounted

**Body Style:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-676-8670

Reliability Indicator:
Not established
Overall Length:
3.062 inches
Body Diameter:
1.094 inches
Shaft Diameter:
0.250 inches
Shaft Length:
2.500 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.562 inches
Overall Diameter:
1.484 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
8.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference

## NSN 5905-00-676-8670

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Locking bushing
Electrical Resistance Per Section:
1.000 megohms single section
Rotary Actuator Travel In Angular Deg:
Between 330.0 and 340.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A002a0