

View Online at <https://aerobasegroup.com/nsn/5905-00-677-4156>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.5620 inches

Pilot Length:

0.0620 inches

Overall Length:

2.688 inches

Undercut Diameter:

1.750 inches

Undercut Width:

0.0930 inches

Body Diameter:

1.750 inches

Angle Of Mounting Hole In Deg:

120.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Body Length:

1.750 inches

Overall Diameter:

1.750 inches

Mounting Lip Diameter:

1.7500 inches

Mounting Lip Depth:

0.0780 inches

Mounting Hole/stud Circle Diameter:

1.250 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

6.00 inch-ounces

Screw Thread Diameter:

0.138 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

3

Terminal Location:

Upper adjacent side two rows

Mounting Method:

Threaded hole

Center To Center Distance Between Terminal Rows:

0.250 inches

Electrical Resistance Per Section:

5.000 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

Power Dissipation Rating Per Section In Watts:

3.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0