## NSN 5905-00-677-4157

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-677-4157

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
0.375 inches
Flat Height:
0.218 inches
Body Diameter:
0.938 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.375 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

## NSN 5905-00-677-4157

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Diss	ipation	Rating	Per	Section	In	Watts:
------------	---------	--------	-----	---------	----	--------

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A002a0