

View Online at <https://aerobasegroup.com/nsn/5905-00-677-4493>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Pilot Diameter:

1.50000 inches

Pilot Length:

0.06200 inches

Overall Length:

2.422 inches

Undercut Diameter:

1.625 inches

Undercut Width:

0.07800 inches

Body Diameter:

1.750 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.937 inches

Body Length:

1.485 inches

Overall Diameter:

2.312 inches

Mounting Lip Diameter:

1.75000 inches

Mounting Lip Depth:

0.09300 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

358.0

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Electrical Resistance Per Section:

25.000 percent, rated amperes c and better industrial clears

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 all sections

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

80.0 all sections

Power Dissipation Rating Per Section In Watts:

3.0 free air all sections

Function Conformity Per Section:

All sections absolute conformity

Resistance Tolerance Per Section In Percent:

-2.0/+2.0 1st section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections equation

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Test Data Document:

99687-240-1264+2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0