Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-677-7860

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Body Diameter:
Between 0.7186 inches and 1.824 inches
Mounting Stud Length:
Between 0.093 inches and 0.236 inches
Body Length:
Between 0.271 inches and 0.689 inches
Actuator Type:
Integral knob
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Fragility Factor:
Moderately delicate
Screw Thread Diameter:
0.073 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
72.0
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Threaded stud
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.2 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
0.000



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

## Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

#### Fiig:

A002a0