

View Online at <https://aerobasegroup.com/nsn/5905-00-679-2820>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.3745 inches and 0.3750 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.7810 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.125 inches

Shaft Length:

1.219 inches

Body Length:

1.571 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0630 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Fragility Factor:

Moderately rugged

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-1.0 to 1.0 degrees angular rotation single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Tap Location From Ccw Terminal Per Section In Ohms:

2500.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0