NSN 5905-00-679-4721

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-679-4721

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Body Length:
1.000 inches
Body Width:
2.000 inches
Body Height:
2.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Maximum Starting Torque:
20.00 inch-ounces
Maximum Running Torque:
20.00 inch-ounces
Screw Thread Diameter:
0.190 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
2
Terminal Location:
Front end
Mounting Method:
Bracket and threaded hole
Features Provided:
Humidity proof
Electrical Resistance Per Section:
100.0 ohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Power Dissipation Rating Per Section In Watts:

5.0 free air single section

NSN 5905-00-679-4721

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0