NSN 5905-00-681-1187

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-681-1187 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Overall Length:** 1.469 inches **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.594 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 2.500 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:**

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

NSN 5905-00-681-1187

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0