## NSN 5905-00-681-4275

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-681-4275 **Section Quantity:** 1 **Body Style:** Rectangular w/tab/flange mounted **Reliability Indicator:** Not established **Thread Length:** 0.900 inches **Overall Length:** 11.700 inches **Overall Height:** 1.600 inches **Overall Width:** 2.000 inches **Mounting Hole Diameter:** 0.201 inches **Shaft Diameter:** 0.1875 inches **Shaft Length:** 5.600 inches **Body Length:** 6.100 inches **Body Width:** 2.000 inches **Body Height:** 1.6000 inches **Shaft Style:** Round, threaded **Actuator Type:** Single shaft **Distance Between Mounting Hole Centers:** Between 1.430 inches and 1.450 inches **Lateral Distance Between Mounting Hole Centers:** Between 5.536 inches and 5.556 inches **Mounting Facility Quantity: Terminal Location:** 

Rear end

**Mounting Method:** 

Unthreaded hole

**Electrical Resistance Per Section:** 

40.000 kilohms single section

## NSN 5905-00-681-4275

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ower Dissipation	n Rating Per	r Section In Watts:
------------------	--------------	---------------------

0.1 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

105.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A002a0