Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-681-4275

Section Quantity:

1

Body Style:

Rectangular w/tab/flange mounted

Reliability Indicator:

Not established

Thread Length:

0.900 inches

Overall Length:

11.700 inches

Overall Height:

1.600 inches

Overall Width:

2.000 inches

Mounting Hole Diameter:

0.201 inches

Shaft Diameter:

0.1875 inches

Shaft Length:

5.600 inches

Body Length:

6.100 inches

Body Width:

2.000 inches

Body Height:

1.6000 inches

Shaft Style:

Round, threaded

Actuator Type:

Single shaft

Distance Between Mounting Hole Centers:

Between 1.430 inches and 1.450 inches

Lateral Distance Between Mounting Hole Centers:

Between 5.536 inches and 5.556 inches

Mounting Facility Quantity:

4

Terminal Location: Rear end Mounting Method: Unthreaded hole

Electrical Resistance Per Section:

40.000 kilohms single section

NSN 5905-00-681-4275

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.1 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

105.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0