## NSN 5905-00-681-4283

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-681-4283 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Height:** 0.360 inches **Overall Width:** 0.360 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.030 inches **Body Length:** 

1.340 inches **Body Width:** 0.300 inches

**Body Height:** 0.360 inches **Shaft Style:** Round, slotted

**Actuator Type:** Single shaft

**Maximum Starting Torque:** 

7.50 inch-ounces

**Lateral Distance Between Mounting Hole Centers:** 

Between 0.995 inches and 1.005 inches

**Mounting Facility Quantity:** 

**Terminal Location:** 

Rear end

**Mounting Method:** 

Unthreaded hole

**Electrical Resistance Per Section:** 

500.000 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

9000.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 single section

## NSN 5905-00-681-4283

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No