Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-681-4330

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.750 inches

#### Shaft Diameter:

0.125 inches

Shaft Length:

0.375 inches

Mounting Bushing Length:

0.250 inches

#### Body Length:

## 0.453 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.375 inches

#### Screw Thread Diameter:

0.250 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# Features Provided:

Nonmetallic shaft

# **Electrical Resistance Per Section:**

50.000 kilohms single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

F single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A002a0