Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-681-4334

#### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Overall Length:**

1.250 inches

#### **Body Diameter:**

1.250 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.625 inches

#### Mounting Bushing Length:

### 0.250 inches

**Body Length:** 

0.625 inches

#### **Overall Diameter:**

1.250 inches

#### Shaft Style:

Round

#### Actuator Type:

Single shaft

### Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.531 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

10.000 kilohms single section

# Power Dissipation Rating Per Section In Watts:

4.0 free air single section



**Resistance Tolerance Per Section In Percent:** 

-2.0 to 2.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0