NSN 5905-00-681-4336

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-681-4336 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Thread Length:** 0.138 inches **Overall Length:** 7.000 inches **Overall Height:** 0.719 inches **Overall Width:** 0.750 inches **Shaft Diameter:** 0.188 inches **Shaft Length:** 1.000 inches **Body Length:** 6.000 inches **Body Width:** 0.750 inches **Body Height:** 0.719 inches **Shaft Style:** Round, threaded **Actuator Type:** Single shaft **Longitudinal Actuator Travel:** 3.000 inches **Longitudinal Actuator Effective Electrical Stroke Length:** 3.000 inches **Screw Thread Diameter:** 0.100 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 28.0 **Mounting Facility Quantity:**

Terminal Location:

Upper adjacent side single row

NSN 5905-00-681-4336

Precision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:	
Threaded hole	
Electrical Resistance Per Section:	
5.000 kilohms single section	
Function Conformity Tolerance Per Section:	
-0.50/+0.50 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
105.0 single section	
Power Dissipation Rating Per Section In Watts:	
5.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
-5.0/+5.0 single section	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
40.0 single section	
Terminal Type And Quantity:	
3 screw	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	