NSN 5905-00-681-4526

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-681-4526

Electrical Resistance: 2.000 kilohms Resistance Tolerance in Percent: 4.1000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 2.050 inches Body Length: 2.050 inches Power Dissipation Rating in Watts: 2.000 free air Style Designator: 4x/ial terminal each end Test Data Document: 83954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 83954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 83954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 83954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 83954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 83954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 83954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 83954-724c595 drawing (this is the basic governing drawing)	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: 1.0004-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire Isaad Reliability Indicator: Note established Body Diameter: 0.250 inches Body Length: 0.656 inches Power Dissipation Rating in Watts: 2.000 free air Style Designator: Avial terminal each end Test Data Document: Style Test Document: 98954-724-6595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wia Unit Of Measure: ————————————————————————————————————	-20.0/+20.0
Resistance Tolerance In Percent: 1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 1275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 10.250 inches Body Length: 10.655 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 159954-724c555 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 159954-724c555 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 150954-724c555 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 150954-724c555 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 150954-724c555 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 150954-724c555 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 150954-724c555 drawing (this is the basic governing drawing) 150954-724c555 drawing (this is the basic governing drawing) 150964-724c555 drawing (this is the basic governing drawing)	Electrical Resistance:
Anbient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 125.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 12.250 inches Body Length: 10.656 inches Power Dissipation Rating In Watts: 12.000 free air Style Designator: Avail terminal each end Test Data Document: 139954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure:	2.000 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Avail terminal each end Test Data Document: 39954-724C595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 20.250 inches Body Length: 20.656 inches Power Dissipation Rating In Watts: 20.00 free air Style Designator: Availa terminal each end Test Data Document: 39954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Avial terminal each end Test Data Document: 39954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wo Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 39954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.250 inches Body Length: 10.656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Avail terminal each end Test Data Document: 189954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 289954-724c595 drawing (this is the basic governing drawing be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Avail terminal each end Test Data Document: 93954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 93954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing drawing) Shelf Life: No Unit Of Measure:	275.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 99954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.856 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 39954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No Fiig:	-55.0/+275.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization: No Filig:	Terminal Type:
Note stablished Body Diameter: D. 250 inches Body Length: D. 656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization: No Fiig:	Wire lead
Body Diameter: 0.250 inches Body Length: 0.656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Reliability Indicator:
Body Length: 0.656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not established
Body Length: 0.656 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Diameter:
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 39954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 39954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
2.000 free air Style Designator: Axial terminal each end Test Data Document: 89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.656 inches
Style Designator: Axial terminal each end Test Data Document: B9954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2.000 free air
Test Data Document: 89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Style Designator:
89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	89954-724c595 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Fiig:	Demilitarization:
	No
4001a0	Fiig:
	A001a0