## NSN 5905-00-681-4639

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-681-4639

**Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.750 inches **Shaft Diameter:** 0.123 inches **Shaft Length:** 0.438 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.988 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.234 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 50.000 ohms 2nd section **Power Dissipation Rating Per Section In Watts:** 

1.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 2nd section

**Standard Taper Curve Per Section:** 

A single section

## NSN 5905-00-681-4639

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal <sup>-</sup>	Type	And	Quantity	<b>/</b> :
-----------------------	------	-----	----------	------------

6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0