NSN 5905-00-681-5287

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-681-5287 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 2.771 inches and 2.853 inches **Body Diameter:** Between 1.796 inches and 1.828 inches **Shaft Diameter:** 0.250 inches Shaft Length: 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** Between 1.990 inches and 2.010 inches **Overall Diameter:** Between 1.999 inches and 2.063 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 1.75 inch-ounces **Maximum Running Torque:** 1.25 inch-ounces **Maximum Stop Torque:** 750.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** Between 0.557 inches and 0.567 inches **Shaft End Play:** 0.00800 inches **Shaft Runout:** 0.002 inches

NSN 5905-00-681-5287

Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Upper adjacent side two rows
Mounting Method:
Standard bushing
Center To Center Distance Between Terminal Rows:
0.250 inches
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
150.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
110.0 single section
Power Dissipation Rating Per Section In Watts:
8.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-681-5287

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0