## NSN 5905-00-681-8790

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-681-8790 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 0.453 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Radius:** 0.245 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 2.5 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

## NSN 5905-00-681-8790

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0