

View Online at <https://aerobasegroup.com/nsn/5905-00-681-9989>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

2.000 inches

**Shaft Diameter:**

0.249 inches

**Shaft Length:**

0.495 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.905 inches

**Shaft Style:**

Round

**Contact Arm Electrical Off Position:**

Fully ccw

**Actuator Type:**

Single shaft

**Shaft End Play:**

0.00500 inches

**Shaft Runout:**

0.001 inches

**Lateral Runout:**

0.004 inches

**Pilot Diameter Runout:**

0.00150 inches

**Shaft Radial Play:**

0.00200 inches

**Screw Thread Diameter:**

0.500 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

50.000 kilohms single section

**Function Conformity Tolerance Per Section:**

-0.25/+0.25 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 single section

**Power Dissipation Rating Per Section In Watts:**

4.8 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-1.0/+1.0 single section

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Terminal Type And Quantity:**

3 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0