## NSN 5905-00-682-0678

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-682-0678

Continu Countities
Section Quantity:
1
Body Style:
Rectangular w/mounting hole/slot
Reliability Indicator:
Not established
Terminal Length:
0.190 inches
Mounting Hole Diameter:
0.074 inches
Shaft Diameter:
0.090 inches
Shaft Length:
0.072 inches
Body Length:
0.380 inches
Body Width:
0.200 inches
Body Height:
0.380 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Center To Center Distance Between Terminals:
0.200 inches
Mounting Facility Quantity:
1
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Unthreaded hole
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## NSN 5905-00-682-0678

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: