NSN 5905-00-682-1325

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-682-1325

View Online at https://aerobasegroup.com/nsn/5905-00-682-1325
Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
Between 1.281 inches and 1.345 inches
Overall Height:
Between 0.296 inches and 0.328 inches
Overall Width:
Between 0.270 inches and 0.290 inches
Mounting Hole Diameter:
0.088 inches
Shaft Diameter:
Between 0.109 inches and 0.141 inches
Shaft Length:
Between 0.047 inches and 0.079 inches
Body Length:
Between 1.234 inches and 1.266 inches
Body Width:
Between 0.270 inches and 0.290 inches
Body Height:
Between 0.296 inches and 0.328 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
Between 0.995 inches and 1.005 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
50.000 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

NSN 5905-00-682-1325

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipati	on Rating Po	er Section Ir	Watts:
-----------------	--------------	---------------	--------

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0