## NSN 5905-00-682-1383



View Online at http	os://aerobasegroup.com/nsn/5905-00-682-1383
Section Quantity	
1	
Body Style:	
Cylindrical bushing	g mounted
Reliability Indicat	or:
Not established	
Overall Length:	
Between 1.312 inc	hes and 1.562 inches
<b>Body Diameter:</b>	
Between 1.032 inc	hes and 1.156 inches
Shaft Diameter:	
Between 0.248 inc	hes and 0.251 inches
Shaft Length:	
Between 0.844 inc	hes and 0.906 inches
Mounting Bushin	g Length:
Between 0.485 inc	hes and 0.515 inches
Body Length:	
Between 0.468 inc	hes and 0.656 inches
Overall Diameter:	
1.515 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Maximum Startin	g Torque:
6.00 inch-ounces	
Maximum Stop To	orque:

128.00 inch-ounces

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

Between 0.515 inches and 0.547 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Locking bushing

## NSN 5905-00-682-1383

**Fiig:** A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
250.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No