NSN 5905-00-682-4031

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-682-4031

Section Quantity:
1
Body Style:
Cylindrical hole/slot mounted
Reliability Indicator:
Not established
Overall Length:
1.313 inches
Body Diameter:
3.093 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.594 inches
Body Length:
0.594 inches
Overall Diameter:
3.093 inches
Mounting Hole/stud Circle Diameter:
0.750 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
250.0
Maximum Starting Torque:
1.50 inch-ounces
Maximum Running Torque:
1.50 inch-ounces
Shaft Runout:
0.001 inches
Screw Thread Diameter:
0.184 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:

NSN 5905-00-682-4031

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
13.700 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0