Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-682-4157

Section Quantity:

Body Style: Cylindrical bushing mounted Overall Length: 1.313 inches

1

Body Diameter:

0.875 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.688 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.250 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.000 kilohms single section

Power Dissipation Rating Per Section In Watts:

12.5 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

NSN 5905-00-682-4157

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section: A single section Special Features: Supplied with no. 5151 ohmite knob Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A002a0