Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-682-9382

| View Online at https://aerobasegroup.com/nsn/5905-00-682-9382 |
|---|
| Section Quantity: |
| 1 |
| Body Style: |
| Cylindrical |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| 0.500 inches |
| Body Length: |
| 0.531 inches |
| Actuator Type: |
| Flush drive with slot-hole |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 360.0 |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Terminal |
| Electrical Resistance Per Section: |
| 10.000 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 120.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.25 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -20.0 to 20.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| |

NSN 5905-00-682-9382

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

