NSN 5905-00-683-2120

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View C	nline at https://aerobasegroup.com/nsn/5905-00-683-2120
Sectio	n Quantity:
1	
Body S	Style:
Cylindr	ical bushing mounted
Reliab	ility Indicator:
Not est	ablished
Overal	I Length:
Betwee	en 1.281 inches and 1.375 inches
Body [Diameter:
Betwee	en 0.890 inches and 0.922 inches
Shaft [Diameter:
Betwee	en 0.248 inches and 0.251 inches
Shaft L	ength:
Betwee	en 0.844 inches and 0.906 inches
Mount	ing Bushing Length:
0.375 i	nches
Body I	Length:
Betwee	en 0.437 inches and 0.469 inches
Overal	I Diameter:
1.274 i	nches
Shaft S	Style:
Round	slotted
Actuat	or Type:
Single	shaft
Maxim	um Starting Torque:
6.00 in	ch-ounces
Maxim	um Stop Torque:
128.00	inch-ounces
Nontui	n Device Location:
At 9 oc	lock
Nontui	n Device Radius:
Betwee	en 0.422 inches and 0.454 inches
Screw	Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-683-2120

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:	
50.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
Between 251.0 and 318.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
120.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Resistance Tolerance Per Section In Percent:	
-10.0 to 10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Test Data Document:	
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;	
xcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental	
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
3 tab, solder lug	
Specification Data:	
81349-mil-r-94/3 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	