Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-683-2898

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Body Diameter:**

1.156 inches

### Shaft Diameter:

0.250 inches

### Shaft Length:

2.000 inches

### Mounting Bushing Length:

0.375 inches

### Body Length:

## 0.625 inches

Shaft Style:

### Round

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

250.000 ohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Standard Taper Curve Per Section:

A single section



## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0