NSN 5905-00-683-5080

Section Quantity:

Cylindrical bushing mounted

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-683-5080

Reliability Indicator:		
Not established		
Body Diameter:		
1.125 inches		
Shaft Diameter:		
0.250 inches		
Shaft Length:		
1.000 inches		
Mounting Bushing Length:		
0.375 inches		
Body Length:		
0.594 inches		
Shaft Style:		
Round		
Actuator Type:		
Single shaft		
Nonturn Device Location:		
At 9 oclock		
Nonturn Device Radius:		
0.531 inches		
Screw Thread Diameter:		
0.375 inches		
Screw Thread Series Designator:		
Unef		
Screw Thready Qty Per Inch (tpi):		
32.0		
Terminal Location:		
Rear end		
Mounting Method:		
Standard bushing		
Electrical Resistance Per Section:		
1.000 kilohms single section		
Power Dissipation Rating Per Section In Watts:		
2.0 free air single section		
Resistance Tolerance Per Section In Percent:		
-10.0 to 10.0 single section		
Standard Taper Curve Per Section:		
A single section		

NSN 5905-00-683-5080

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Termi	nal Type And	Quantity:
3 tab,	solder lug	

o tab, solder la

Shelf Life: N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0