

View Online at <https://aerobasegroup.com/nsn/5905-00-683-5600>

**Section Quantity:**

2

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.0620 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

0.875 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

0.875 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.060 inches

**Body Length:**

1.571 inches

**Mounting Lip Diameter:**

0.8750 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

354.0

**Maximum Starting Torque:**

0.10 inch-ounces

**Maximum Running Torque:**

0.10 inch-ounces

**Shaft End Play:**

0.00500 inches

**Shaft Runout:**

0.001 inches

**Lateral Runout:**

0.003 inches

**Pilot Diameter Runout:**

0.00150 inches

**Shaft Radial Play:**

0.003 inches

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

2.000 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.25/+0.25 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.5 free air single section

**Function Conformity Per Section:**

All sections independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 all sections

**Terminal Type And Quantity:**

6 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0