

View Online at <https://aerobasegroup.com/nsn/5905-00-683-6451>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

0.245 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.500 inches

**Mounting Bushing Length:**

0.310 inches

**Body Length:**

0.453 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Front end

**Mounting Method:**

Standard bushing

**Cubic Measure:**

0.021 cubic inches

**Electrical Resistance Per Section:**

500.000 ohms single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Test Data Document:**

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:**

81349-mil-r-94/3 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0