

View Online at <https://aerobasegroup.com/nsn/5905-00-683-6489>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.7470 inches and 0.7500 inches

Pilot Length:

Between 0.0520 inches and 0.0720 inches

Overall Length:

1.193 inches

Undercut Diameter:

Between 0.747 inches and 0.750 inches

Undercut Width:

0.0630 inches

Body Diameter:

Between 0.865 inches and 0.885 inches

Shaft Diameter:

0.125 inches

Shaft Length:

Between 0.380 inches and 0.400 inches

Body Length:

0.803 inches

Overall Diameter:

1.067 inches

Mounting Lip Diameter:

Between 0.8650 inches and 0.8850 inches

Mounting Lip Depth:

Between 0.0520 inches and 0.0720 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

354.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Flange

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

110.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-2.0/+2.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0