Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-686-2645

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# Reliability Indicator:

Not established

## **Overall Length:**

1.312 inches

## **Overall Height:**

0.312 inches

## **Overall Width:**

0.280 inches

## Mounting Hole Diameter:

0.086 inches

## Shaft Diameter:

# 0.125 inches

Shaft Length:

## 0.062 inches

Body Length:

# 1.250 inches

Body Width:

#### 0.250 inches

**Body Height:** 

#### 0.312 inches

Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

#### Fragility Factor:

Moderately rugged

## Lateral Distance Between Mounting Hole Centers:

1.000 inches

## **Mounting Facility Quantity:**

2

Terminal Location:

Rear end

# Mounting Method:

Unthreaded hole

# **Electrical Resistance Per Section:**

20.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

9000.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0