

View Online at <https://aerobasegroup.com/nsn/5905-00-686-3367>

Section Quantity:

3

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.468 inches

Body Diameter:

Between 1.125 inches and 1.188 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

0.547 inches

Mounting Bushing Length:

0.250 inches

Body Length:

Between 1.844 inches and 1.969 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Nonturn Device Location:

At 3 o'clock and at 9 o'clock

Nonturn Device Radius:

0.578 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.0 kilohms 3rd section

Power Dissipation Rating Per Section In Watts:

1.27 free air 3rd section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0