NSN 5905-00-686-3733

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-686-3733 **Section Quantity:** 2 **Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 3.359 inches **Body Width:** 1.969 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

Electrical Resistance Per Section: 50.000 ohms all sections

Power Dissipation Rating Per Section In Watts:

25.0 free air all sections

NSN 5905-00-686-3733

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Resistance | Tolerance | Per | Section | In | Percent: |
|------------|------------------|-----|---------|----|----------|
| | | | | | |

-10.0 to 10.0 all sections

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0