

View Online at <https://aerobasegroup.com/nsn/5905-00-686-4097>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.063 inches

Body Diameter:

Between 0.469 inches and 0.531 inches

Shaft Diameter:

Between 0.120 inches and 0.130 inches

Shaft Length:

Between 0.422 inches and 0.453 inches

Mounting Bushing Length:

Between 0.219 inches and 0.281 inches

Body Length:

0.625 inches

Overall Diameter:

Between 0.469 inches and 0.531 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Maximum Starting Torque:

7.00 inch-ounces

Nonturn Device Location:

At 10'30 oclock

Nonturn Device Radius:

Between 0.152 inches and 0.192 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

315.0

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-2.0 to 2.0 single section

Actuator Travel Control Feature:

Stops

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

60.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0