## NSN 5905-00-686-9888

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-686-9888

Seedien Overstitus
Section Quantity:
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.094 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.440 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.187 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.500 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

## NSN 5905-00-686-9888

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature in Deg Ceisius Per Section At Full Rated Powers
70.0 single section
Standard Taper Curve Per Section:
A single section

**Terminal Type And Quantity:** 

3 solder stud

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0