## NSN 5905-00-686-9989

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-686-9989

Electrical Resistance: 3.000 kilohms Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +50.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
3.000 kilohms Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +50.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a	-20.0/+20.0
Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +50.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +50.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a	3.000 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +50.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: +50.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a	-3.000/+3.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: +50.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: +50.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a	50.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: +50.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
https://doi.or.width.com/html/html/html/html/html/html/html/htm	275.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.312 inches  Body Length: 1.000 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator: Axial terminal each end  Shelf Life: N/a	+50.0/+275.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Shelf Life: N/a	Inclosure Method:
Wire lead  Reliability Indicator: Not established  Body Diameter: 0.312 inches  Body Length: 1.000 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator: Axial terminal each end  Shelf Life: N/a	Encapsulated
Reliability Indicator: Not established  Body Diameter: 0.312 inches  Body Length: 1.000 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator: Axial terminal each end  Shelf Life: N/a	Terminal Type:
Not established  Body Diameter: 0.312 inches  Body Length: 1.000 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator: Axial terminal each end  Shelf Life: N/a	Wire lead
Body Diameter:  0.312 inches  Body Length:  1.000 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	Reliability Indicator:
0.312 inches  Body Length:  1.000 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	Not established
Body Length:  1.000 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	Body Diameter:
1.000 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	0.312 inches
Power Dissipation Rating In Watts: 5.000 free air  Style Designator: Axial terminal each end  Shelf Life: N/a	Body Length:
5.000 free air  Style Designator:  Axial terminal each end  Shelf Life:  N/a	1.000 inches
Style Designator: Axial terminal each end Shelf Life: N/a	Power Dissipation Rating In Watts:
Axial terminal each end  Shelf Life: N/a	5.000 free air
Shelf Life: N/a	Style Designator:
N/a	Axial terminal each end
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
Demilitarization:	Demilitarization:
No	No
Fiig:	Fiig:
A001a0	A001a0