NSN 5905-00-688-3370

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-688-3370 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.220 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 269.5 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Mounting Method:** Flange **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 4.211 kilohms single section Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: 97.7 single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -0.6 to 0.6 degrees angular rotation single section **Resistance Tolerance Per Section In Percent:** -1.0 to 1.0 single section **Actuator Travel Control Feature:** Stops **Standard Taper Curve Per Section:** A single section

Terminal Type And Quantity: 6 solder stud

NSN 5905-00-688-3370

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0