NSN 5905-00-688-3469

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-688-3469 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.312 inches **Body Diameter:** 1.625 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.562 inches **Overall Diameter:** 2.031 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 275.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.812 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

Electrical Resistance Per Section: 5.000 kilohms single section

NSN 5905-00-688-3469

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: 294.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -20.0 to 20.0 single section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** Demilitarization: No