

View Online at <https://aerobasegroup.com/nsn/5905-00-688-4476>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.671 inches

Body Diameter:

Between 0.828 inches and 0.891 inches

Shaft Diameter:

Between 0.123 inches and 0.125 inches

Shaft Length:

0.437 inches

Mounting Bushing Length:

Any acceptable

Body Length:

Between 0.609 inches and 0.641 inches

Overall Diameter:

0.922 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.219 inches and 0.250 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

500.000 kilohms 2nd section

Power Dissipation Rating Per Section In Watts:

0.2 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 2nd section

Standard Taper Curve Per Section:

A single section

Special Features:

0.375 inch long bushing

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0