## NSN 5905-00-688-4511

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-688-4511 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.515 inches **Terminal Length:** 0.203 inches **Overall Height:** 0.312 inches **Overall Width:** 0.220 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.094 inches **Shaft Length:** 0.062 inches **Body Length:** 1.250 inches **Body Width:** 0.220 inches **Body Height:** 0.312 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Center To Center Distance Between Terminals:** 0.690 inches **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** 

Rear end

**Mounting Method:** 

Unthreaded hole

## NSN 5905-00-688-4511

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.000 ohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.310 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Power Dissipation Rating Per Section In Watts:
0.08 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
49956-e-5272a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0